

SPECIFICATION SHEET

NEW & IMPROVED!

A SERIES SPRINGWOUND AUTO OFF IN-WALL TIME SWITCH

APPLICATIONS

- Whole house fans
- Indoor/Outdoor lighting
- Bathroom fans and lights
- Self storage

FEATURES

VARIABLE TIMING:

Twist knob for time ON setting. Time ON lengths from 15 minutes to 12 hour vary by model.

HOLD FEATURE:

Some models have position for constant ON.

EASY SET:

No adjustments. Just wire and go!

EASY WIRING:

No neutral required. Great for retrofit! Use as single or in multi-gang box with no de-rating.

SWITCH TYPE:

> **SPDT "2-in-1" contacts wire as SPST also.**

COLOR:

Ivory, Light Almond, and White available.

WALL PLATE:

Fits standard or decorator style wall plates, see below (not included).

INPUT VOLTAGE:

125/250/277 VAC 50/60 Hz.

TERMINAL SIZE:

#12AWG.

OPERATING TEMPERATURE:

32°F to 122°F (0°C to 50°C).

CAUTION: This timer is not to be used in precision timing applications where inaccurate timing could have dangerous consequences (i.e. sun lamp, sauna, etc.)




WIRING DIAGRAM

USE FOR SPST



USE FOR SPDT




CONTACT RATINGS

TYPE	VOLTAGE	RATING
Resistive	125VAC	20A
	250VAC	10A
	277VAC	10A
Inductive	125VAC	20A
	250VAC	10A
	277VAC	10A
Tungsten	125VAC	7A
Motor	125VAC	1HP
	250VAC	2HP

WALL PLATE ASSEMBLY

(Wall plate not included)



www.aybwatersolutions.mx